

General International "MAXI-LATHE VF" Wood Lathe Model 25-114QC

Features:

- Forward or reverse spindle rotation selector switch for precision workpiece sanding and polishing
- Quick lock control levers easily position tool rest
- Maximum distance of 17" between centers
- Stable, cast iron frame, head and tailstock to reduce chatter and vibration for smoother turning
- Maximum distance of 40" between centers with optional bed extension (item 25-116)
- Quick release lever for quick belt positioning changes
- 3 Variable Speeds: 250-800, 550-1700 & 1200-3600 RPM
- Digital spindle speed display
- Features positive indexing in 15° increments total 24 indexing positions
- Heavy duty 1" diameter tool rest post

Specifications:

Spindle Speed	250-3600 RPM
Swing Over Bed	14" (356 mm)
Swing Over Tool rest	10-3/4" (273 mm)
Distance Between Centers	17" (432 mm)
Spindle Thread	1" - 8 TPI
Tailstock through hole	3/8" diameter (10 mm)
Morse Taper	MT#2 (headstock & tailstock)
Self Ejecting Travel	2" (51 mm)
Tool Rest	6" (152 mm)
Face Plate	3" (76 mm)
Indexing positions	24 x 15°
Motor	3/4HP, 110V, 5A, 1950 RPM
Weight	93 lbs. (42.5 kg)