

# King Gearhead Drilling Machine Model KC-50

## Features:

- Powerful 2HP motor
- Magnetic line interruption switch and safety guard with limit switch protection
- Quill has an internal MT#4 to accept tapered drill press accessories
- Feed selector dial and automatic power downfeed lever and tapping
- Production sized table with coolant trough and clamping slots
- Positive depth stop for quick and easy adjustment
- Built in tool ejector
- Comes with 5/8" (JT#33) drill chuck, chuck key, MT#4 chuck arbor, MT#4-MT#2 sleeve, MT#4-MT#3 sleeve, recirculating coolant system, work light, retractable transparent guard, drift key and tool box

## Specifications:

Drilling Capacity in light alloy steel	1-3/8"
Drilling Capacity in mild steel	1-1/2"
Chuck Size	5/8"
Spindle Taper	MT#4
Swing	27-1/2"
Stroke	7"
Max Distance spindle to table	26"
Max Distance spindle to base	43"
Table Dimensions	22" x 22"
Size of T-slot on table	5/8"
Speeds	18(60-870 / 120-1740) RPM
Motor	2.4 Amp
Coolant Pump motor	1/8 HP
Voltage	550V 3 phase 60 Hz
Assembled Dimensions (LxWxH)/Weight	22" x 37" x 91"/1200 lbs
Packaging Dimensions (LxWxH)/Weight	83-3/4" x 24-7/8" x 44-1/4'/1309 lbs

