

King Milling Drilling Machine Model KC-20VS

Features:

- Powerful 1HP single phase DC motor
- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Spindle depth digital readout and control panel with metric and imperial readings
- Spindle RPM digital readout
- Spindle depth fine feed knob
- Forward/reverse switch and variable speed selector dials
- Comes with 1/2" chuck, chuck key, R8 chuck arbor, safety guard, 2T-bolts, oil bottle, adjustment wrenches, hex. keys and tool box

Specifications:

Drilling Capacity in cast iron	3/4"
Drilling Capacity in steel	5/8"
Max. Distance Spindle Nose to Table	13"
Swing	13"
Spindle Taper	R8
Spindle Stroke	2"
Variable Speeds	2 (50-1125/100-2250) RPM
Face Mill Capacity	2-1/2"
Cross Travel	6-7/8"
Size of T-slot on Table	1/2"
Motor	4.8 amp, 5600 RPM
Voltage	110V, 1 ph. 60 Hz
Working area of the Table	7-1/16" x 27-1/2"
End Mill Capacity	3/4"
Max. Longitudinal Travel	18-7/8"
Assembled Dimensions	27-1/2" x 29-5/8" x 35-3/8"/264 lbs
Package Dimensions	17-1/2" x 16-1/2" x 32-1/2"/308 lbs.