

King 14" x 40" Gearhead Metal Lathe Model KC-1440ML-2

Features:

- Powerful 2HP motor
- 2" Spindle bore capacity
- Safety guard with limit switch protection
- Line interruption switch system needs a restart after a power failure
- Guideway and gears in headstock are all hardened and precision ground
- Spindle foot brake incorporated in the cabinet stand for easy operation and reliable safety
- Come complete with 6" 3 jaw chuck, 8" 4 jaw chuck, imperial and metric gears, quick change tool post, steady rest, follow rest, 12" D1-4 camlock face plate, coolant system, full length splash guard, thread chasing dial indicator, 2 MT#3 dead centers, JT#5-MT#3 sleeve, chip tray, tool box, halogen lamp, chuck keys, hex. keys and cabinet stand (with foot brake incorporated)

Specifications:

Distance Between Centers	40"
Swing Over Bed	14"
Spindle Bore	2"
Swing Over Cross Slide	8-5/8"
Taper in Headstock	MT#6
Taper in Tailstock	MT#3
Width of Bedways	7-5/16"
Total Travel of Cross Slide	6-3/16"
Total Travel of Top Slide	3-1/2"
Spindle Speeds	8 (70-2000) RPM
Thread Cutting Range	34 (4-56 tpi) 26 (.4-7 mm)
Motor	11A, 240V, 1Ph, 60 Hz
Dimensions (lxwxh)	75" x 32" x 53"
Weight	2025 lbs.