

King Combo Lathe/Mill

Model KC-1620CLM

Features:

- Two powerful 3/4HP 110V motor
- Lathe chuck and drill chuck safety guards with limit switch protection and standard tool post safety guard
- Easily change from lathe mode to mill mode
- Forward/reverse switch for both operating modes
- Bedways are hardened and precision ground
- Comes with 5" 3 jaw chuck, imperial and metric change gears, quick change tool post, steady rest, follow rest, thread chasing dial indicator, MT#3 and MT#4 dead centres, 1/2" drill chuck and tool box with adjusting tools

Specifications:

Distance between Centers	20"
Swing over Bed	16-1/2"
Spindle Bore	1-1/8"
Headstock/Tailstock Tapers	MT#4/MT#3
Cross Slide Travel	8"
Lathe Spindle Speeds	7 (160-1360 RPM)
Thread Cutting Range	36 (4-120 TPI) 22 (0.2-6mm)
Automatic Feeding Range	0.002-0.014"/0.05-0.35mm
Drilling/Face Mill/End Mill Capacities	7/8" - 1-1/8" - 3-1/8"
Max. Distance Spindle Nose to Milling Table	12"
Drilling Speeds	16 (120-3000 RPM)
Motors (Lathe/Mill)	3/4HP, 110V, 9 Amp, 1 Ph., 60Hz
Assembled Dimensions (LXWXH)/Weight	43" x 19-1/2" x 38"/515 lbs.
Package Dimensions (LXWXH)/Weight	45" x 23" x 42"/615 lbs.