

King Milling Drilling Machine

Features:

- New and improved model with fwd/rev switch
- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Pulley cover with limit switch protection
- Spindle is equipped with four heavy-duty tapered roller bearings
- Table control hand wheels have large micrometer dials graduated in .001"
- Head swivel 360 degrees and is easily raised and lowered
- Comes with 3" face cutter, 1/2" chuck with key, 3-1/2" angle vise and safety guard

Specifications:

Drilling Capacity	1-1/4"
Max. Dist Spindle Nose to Table	18-7/8"
Swing	16-1/2"
Spindle Taper	R8
Spindle Stroke	5"
Diameter of Column	4-3/4"
Speeds	12 (150-2500) RPM
Face Mill Capacity	3"
End Mill Capacity	3/4"
Max. Longitudinal Travel	17"
Cross Travel	7-1/4"
Working Area of Table	8-1/4" x 28-3/4"
Size of T slot on Table	5/8"
Motor	11 Amp 220V, 1 Phase, 60 Hz
Assembled Dimensions (lxwxh)	43" x 39" x 42"/502 lbs
Packaging Dimensions (lxwxh)	30-1/4" x 32" x 43-3/8"/600 lbs